

A Higher Level of Precision...A Higher Level of Performance

Rugged General Purpose Toploading Scale

- Large Display
- 6,000 Divisions



Model	XM - 3000	XM - 6000	XM - 15K	XM - 30K
Capacity	3000 g / 6.6 lb	6000 g / 13.2 lb	15 kg / 33 lb	30 kg / 66 lb
Readability	0.5 g / 0.001 lb / 0.02 oz	1 g / 0.002 lb / 0.05 oz	0.002 kg / 0.005 lb / 0.1 oz	0.005 kg / 0.01 lb / 0.2 oz
Divisions	6,000			
Weighing Units / Functions	g / lb / lb : oz		kg / lb / lb : oz	
Stabilization Time (seconds)	< 1.5			
Tare Range	To capacity by subtraction			
Power Source	Built-in rechargeable battery or external power adapter (included)			
Construction	ABS pan with stainless steel insert and ABS housing			
Display	1 inch / 25.4 mm wide viewing angle LCD			
Pan Size (W x D)	9.84 x 8.46 inches / 250 x 215 mm			
Dimensions (W x D x H)	9.4 x 11.2 x 4.1 inches / 240 x 285 x 105 mm			
Operating Environment	32° ~ 104° F non condensing R.H. ≤ 85%			
Net Weight	5.9 lb / 2.67 kg			
Shipping Weight	11 lb / 5 kg			
Options	Spirit level, External power adapter, EL backlight, Secondary rear panel mount display, RS232C interface, Stainless steel pan cover			

XM Series



Features

- Heavy duty construction with overload and underload stops
- Low profile, compact size
- Reads in grams, pounds and pounds : ounces
- Built-in rechargeable battery or external power adapter
- Auto zero tracking
- Automatic power save
- Low battery indicator
- Auto-calibration function
- Adjustable feet
- Wide-angle LCD display
- In use cover

Benefits

- Will withstand harsh industrial operation
- Uses less counter space
- Flexibility of operation
- Portability - battery lasts a minimum of 150 hours (without backlight)
- Ensures that you always start weighing at zero
- Conserves battery power
- Alerts you to change the battery, saving downtime
- Ensures accuracy
- Scale remains level for accurate results on uneven working surfaces - Anti-slip
- Can be seen from a wide viewing range
- Keeps scale clear from contamination